



Rated current/voltage: 15A 250V
 Operation limit voltage: 400V
 Withstanding voltage: 1500
 Insulation resistanceDV500V: 2000MΩ
 Contact resistanceDC1A: 10mΩ

技术要求 (Techique Request):

- 1.外表光滑, 周边无毛刺
(Sleek in appearance, no burrs in periphery);
- 2.螺纹旋入顺畅
(Thread can screw in smoothly);
- 3.与母座配插顺畅
(It should match the male connector smoothly).

9		本体(BODY)	1	BAKELITE	
8		螺丝(BOLT)		A3	
7		连接螺帽(JOINT NUT)	1	ZZnA14-1	镀镍(NICKEL PLATED)
6		孔座盖(CONE PILLAR COVER)	1	BAKELITE	
5		插孔(FEMALE PIN)	4	H62	镀金(GOLD PLATED)
4		塑管(PLASTIC TUBE)	1		
3		锌壳(DIE-CAST SHELL)	1	ZZnA14-1	镀镍(NICKEL PLATED)
2		螺丝(BOLT)	2	A3	镀镍(NICKEL PLATED)
1		压线盖(WIRE-CLAMP COVER)	1	ZZnA14-1	镀镍(NICKEL PLATED)
序号	图号	名称	数量	材料	备注

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION

照片框

ORDER INFORMATION

M25-SA-04-LF
 SERIES | LEADFREE
 04 WAY
 ASSEMBLY
 FEMALE

DESCRIPTION: