



1. MATERIAL
INSULATION: THERMOPLASTIC UL94V-0
COLOR: BLACK.
CONTACT: BRASS
SHELL: BRASS
2. PLATING
CONTACT: GOLD 5u"
Shell: NICKEL 100u"
3. SPECIFICATION
CURRENT: 2 A.
OPERATING TEMPERATURE: -20° C TO 105° C.
INSULATION RESISTANCE: 1000 MEGAOHMS MIN.
DIELECTRIC STRENGTH: 500V AC MIN.
4. Waterproof test:
Reference to IEC 60529 Edition
2.1:2001-02-IP67

Item	Description	Material	UL File No.
1	Insulation	1403G6	E130155
2	Pin	C3604	
3	Shell	C3604	
4	O-Ring	NBR	

BOM	
4	CONTACT
1	SHELL
1	HOUSING
数量	零件

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

M8-PM-04-LF
SERIES | LEADFREE
| 04 WAY
| MOLDING
MALE

DESCRIPTION: M8-4PIN(M) 線端