



NOTE:

SECTION AA

1. MATERIAL :
  - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
  - 1-2. CONTACT : COPPER ALLOY
  - 1-3. SHELL : COPPER ALLOY
  - 1-4. NUT : COPPER ALLOY
  - 1-3. O-RING : NBR ; COLOR : BLACK
2. FINISH :
  - 2-1. CONTACT :10 MICRO INCHES MIN. GOLD PLATING OVER NICKEL
  - 2-2. SHELL : SEE TABLE A
  - 2-2. NUT : NICKEL PLATED 60u" ~ 100u" OVER ALL
3. ELECTRICAL SPECIFICATION :
  - 3-1. Rated current : 5A
  - 3-2. Voltage :125V
  - 3-3. Water proof: IPX7
4. Environmental :
  - 4-1. Operation Temperature : -40 ℃~85℃

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1 : 1

.XX±

DATE

.XXX±

ANG±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

M8-PS-04-LF  
SERIES | LEADFREE  
04 WAY  
SOLDER  
MALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: M8-4PIN(M) 線端