



Assembly

NOTE:

1. MATERIAL :
  - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
  - 1-2. CONTACT : COPPER ALLOY
  - 1-3. O-RING : NBR ; COLOR : BLACK
  - 1-4. NUT : COPPER ALLOY
2. FINISH :
  - 2-1. CONTACT :
    - CONTACT AREA : 10 MICRO INCHES MIN. GOLD PLATING
    - SOLDER AREA : Gold Flash
    - UNDER PLATE : NICKEL
  - 2-2. NUT : NICKEL PLATED 60u" ~ 100u" OVER ALL
3. ELECTRICAL SPECIFICATION :
  - 3-1. Rated current : 5A
  - 3-2. Voltage : 125V
  - 3-3. Water proof: IPX8
4. Environmental :
  - 4-1. Operation Temperature : -20 ℃~85℃

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION

照片框

ORDER INFORMATION

M8-SS-03-LF  
SERIES | LEADFREE  
| 03 WAY  
| SOLDER  
| FEMALE

DESCRIPTION: