



**\*\*\*CONSTRUCTION:**

1.WIRE: \* UL 1061 24AWG OD:1.1mm.

**\*\*\*CONNECTORS:**

2.M8-3M: \* M8-3PIN MALE SOLDER TYPE FOR PANEL MOUNT.  
 \* PINS: BRASS WITH GOLD PLATED.  
 \* INSULATOR: PBT BLACK UL94V-0 RATED.  
 \* SHELL: BRASS WITH NICKEL PLATED.  
 \* GASKET: SILICONE RUBBER BLACK COLOR.  
 \* NUT: BRASS WITH NICKEL PLATED.

3.SHRINK TUBE: \*  $\phi$ 1.5\*15mm BLACK.

4.TEST : \* CT:2 Ohm IS:10M ohm.

5.PACKING: \* PACK EACH CABLE IN A POLY BAG.

6.MATERIAL: \* MATERIAL WITH RoHS GRADE.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X.  $\pm$

.X  $\pm$

.XX  $\pm$

.XXX  $\pm$

ANG  $\pm$

PPOJECTION

照片框

**ORDER INFORMATION**

M8X1-030024W1PBNO-M50C-LF

SERIES

03 WAY

WIRE  
24 AWG

PANEL+BACK+NUT+RING

LEADFREE

500mm

MALE

DESCRIPTION: