



A	線色	B
1	紅	1
2	白	2
3	綠	3
4	黑	4

MBPH-5B04-E50C-LF
LEADFREE
RoHS Compliant

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5Ω
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY
1	CABLE:	UL/CSA 2725 #28*1PR(白,綠)+#28*2C(紅,黑) +AEB 外被:黑色 OD:∅3.5±0.15 USB2.0	OR EQ 1pcs
2	CONN:	MINI USB B TYPE M 焊接式 黑膠芯 PIN鍍金	OR EQ 1set
3	外模料:	PVC 45P 黑色 模號:GH-181	OR EQ 5G
4	HOUSING:	PH-H-04	OR EQ 1pcs
5	TERMINAL:	PH-T-22	OR EQ 4pcs
6	H.S TUBE:	4.0∅15 黑 F32	OR EQ 1pcs
7			

	PART NO. MBPH-5B04-E50C		TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± ANG	DESCRIP TION:			
	DWG NO. MBPH-5B04-E50C						
焯倫股份有限公司	FILE NO.		DRAWING BY	AREA	REVISIONS	HK	DATE
	UNIT / mm	SCALE 1:1	PROJECTION				