



PIN OUT:

P1		P2
1	red(28awg)	1
2	white(28awg)	2
3	green(28awg)	3
4	black(28awg)	4
shell	drain+braid	shell

ITEM	PART NO.	DESCRIPTION	Q' TY
1	5075A-02-02-F1	USB A MALE INSULATOR WHITE MOLDING TYPE	1
2	5075MA-04-M-F1	MINI USB A MALE INSULATOR BLACK MOLDING TYPE	1
3	810B64USB2828B3.8BG3 UL	2725 28AWG/1P+28AWG/2C+AEB OD:3.8mm COLOR :BEIGE 2.0REV	
4	827-PVC-45P-BG	45P PVC MOLDING COLOR BEIGE	
5	829A-R14.2*28.5*6.7	FERRITE CORE OD*H*ID=14.2*28.5*6.7MM	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X.±

.X±

.XX±

.XXX±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MBUB-4H4A2V28FCBE-M1M8-LF

SERIES

28 AWG

REV 2.0

FERRITE CORE

BEIGE

MALE TO MALE

LEADFREE

1800mm

4 PIN H2 TYPE TO 4 PIN A TYPE

DESCRIPTION: USB A/M To Mini USB A/M Cable Ass'y