



PIN OUT(接點)

A		B	COLOR
1	——	1	RED
2	——	2	WHITE
3	——	3	GREEN
4	——	5	BLACK
SHELL	——	SHELL	DRAIN

注意:

1. USB插頭的插拔次數須5000次以上, 且每插拔1000次須進行阻抗記錄, 並把數據記錄在檢驗報表上.
2. 成品出貨須附搖擺測試報告. (累計50000pcs做一份)

ELECTRICAL PROPERTIES:

1. 100% Open Short Mis-Wire Test
2. Contact Resistance: 3 ohm max
3. Insulation Resistance: 10mega ohm min
4. Hipot test: DC 300V 10ms

4	OUTSIDE MOLD 45P PVC COLOR: BLACK	14	G
3	MINI USB 5P BLACK INSULATED OUT 4 PIN(超薄式)	1	SET
2	USB "A" TYPE MALE BLACK INSULATED	1	SET
1	UL2725 28AWG/1P+28AWG/2C+AEB(AL) OD: 3.5±0.1mm JACKET COLOR: BLACK	1	PC
NO.	DESCRIPTION	QTY	UNITS

RoHS Compliant

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE
SIZE A4 PPROJECTION

TOLERANCES ARE

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

MBUB-5B4A28-M23C-LF
SERIES | LEADFREE
230mm
MALE TO MALE
28AWG
5B TO 4A TYPE

DESCRIPTION: