



ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:5MΩ
- 3.CONTACT RESISTANCE:10Ω
- 4.HI-POT:300V 10MS

Pin Assignment		
AF	5MB	COLOR
1 —	1 —	RED
2 —	2 —	WHITE
3 —	3 —	GREEN
4 —	5 —	BLACK
SHELL —	SHELL —	BRAID

NO.	DESCRIPTION	Q'TY	UNITS
4	P.V.C MOLDING 55P COLOR: BLACK		
3	MINI USB 5PIN B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
2	USB A TYPE FEMALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
1	CABLE: UL2725 28/1P+28#/2C+AEB REV 2.0 JACKET COLOR: BLACK OD: 3.5	1	pcs

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MBUB-5B4A2V28-E70C-LF

SERIES

LEADFREE
700mm
MALE TO FEMALE
28 AWG
2.0 REV
5 PIN B TYPE TO 4 PIN A TYPE

DESCRIPTION: