



PIN OUT:

P1		P2
1	red(28awg)	1
2	white(28awg)	2
3	green(28awg)	3
4	black(28awg)	4
shell	drain+braid	shell

Label:



ITEM	PART NO.	DESCRIPTION	Q'TY
1	5075A-02-02-30-F1	USB A MALE INSULATOR WHITE MOLDING TYPE 30U"	1
2	5075MB-05-MS-30-F1	MINI USB B MALE INSULATOR BLACK MOLDING TYPE 30U"	1
3	810B64USB2828B3.8BK3	UL 2725 28AWG/1P+28AWG/2C+AEB OD:3.8mm COLOR :BLACK 2.0REV	
4	827-PVC-50P-BK	50P PVC MOLDING COLOR BLACK	
5	829A-R9.5*19.5*5.0	FERRITE CORE OD*H*ID=9.5*19.5*5.0MM	

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PJECTION

照片框

ORDER INFORMATION

MBUB-5B4A2V28FC-M1M5-LF

SERIES

5 PIN B TYPE TO 4 PIN A TYPE

LEADFREE

1500mm

MALE TO MALE

FERRITE CORE

28 AWG

2.0 REV

DESCRIPTION: USB CABLE(2.0 version)