



5PIN
FEMALE B

ELECTRONIC TEST:
 1.OPEN/SHORT/INTERMITTE:100%.
 2.INSULATION RESISTANCE:5MΩ.
 3.CONTACT RESISTANCE:10Ω.
 4.HI-POT:300V DC/10MS.

Pin Assignment		
MUSB5MB	COLOR	MUSB5FB
1	RED	1
2	WHITE	2
3	GREEN	3
5	BLACK	5
SHELL	DRIAN	SHELL

NO.	DESCRIPTION	UNIT	QT'Y
4	MINI USB 5PIN B TYPE FEMALE SHELL PLATED:NICKEL CONTACT:G/F	PCS	1
3	CABLE: UL2725 28/1P+28#/2C+AEB REV 2.0 JACKET COLOR: BLACK OD: 3.5±0.1mm	PCS	1
2	PVC 55P MOLDED BLACK IN COLOR	PCS	1
1	MINI USB 5PIN B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	PCS	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY		X.± .X± .XX± .XXX± ANG±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1:1	
DATE		
SIZE A4	PJECTION	



ORDER INFORMATION

MBX2-5B5BR28-A1M-LF
 SERIES | LEADFREE
 | 1000mm
 | FEMALE TO MALE
 | 28 AWG
 | 5 PIN TO 5 PIN 90° B TYPE

DESCRIPTION: