



PCB LAYOUT

Specifications:

Current Rating:3.0A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:15m ohm. Max.
 Insulation Resistance:1000M ohm. Min.
 Withstanding Voltage:600V AC/Minute
 Operating Temperature Range:-40°C To +105°C

Material And Finish:

Insulator:PBT (UL94V-0)
 Insulator Color:Black
 Contact:Copper Alloy
 Plating: See How to order

Circuits	Dim.A	Dim.B
2	2.54	7.62
3	5.08	10.16
4	7.62	12.70
5	10.16	15.24
6	12.70	17.78
7	15.24	20.32
8	17.78	22.86
9	20.32	25.40
10	22.86	27.94
11	25.40	30.48
12	27.94	33.02

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X ±
 .X ± 0.20
 .XX ± 0.15
 .XXX ±
 ANG ±

PJECTION

照片框

ORDER INFORMATION

MCG-DS15-1Xxx-LF

SERIES | LEADFREE

1X02:02WAY
 1X12:12WAY

CONTACT AREA GOLD 15u"
 DIP 180°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 2.54mm Pocket Header Straight Single Row