



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 6T,UL94V-0
 Color: Black

Circuit No.	Dimensions	
	A	B
03P	5.08	10.17
04P	7.62	12.71
05P	10.16	15.25
06P	12.70	17.79
07P	15.24	20.33
08P	17.78	22.87
09P	20.32	25.41
10P	22.86	27.95
11P	25.40	30.49
12P	27.94	33.03

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE
 SIZE A4 PPROJECTION

X ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 ANG ±

照片框

ORDER INFORMATION

MCG-VXC-1XxxL-LF
 SERIES L LEADFREE L TYPE FOOT
 1X03:03 WAY
 1X12:12 WAY
 180°SMT CAP NON POST

DESCRIPTION: 2.54mm PITCH 180° WAFER-SMT TYPE