



P1	9	RED	RED	1	P2
	7	WHITE	WHITE	2	
	5	GREEN	GREEN	3	
	3	BLACK	BLACK	4	
	10	RED	RED	1	P3
	8	WHITE	WHITE	2	
	6	GREEN	GREEN	3	
	4	BLACK	BLACK	4	

WIRING TABLE

Electronics Test :

1. Contact Resistance : 2 Ω Max.
2. 100% open & short test (set at 20 KΩ)
3. At DC = 300V , Insulation Resistance : 20 MΩ Min.
4. Test Condition : Temperature : 25 ± 5°C , Humidity : 50% RH Max.

6	HEAT SHRINKABLE TUBE, ø5.0mm, L = 15.0mm, BLACK	4 PCS
5	SOCKET CONTACT	8 PCS
4	HOUSING, 4-POS., 2.54mm PITCH, BLACK	2 PCS
3	SOCKET CONTACT	8 PCS
2	HOUSING, 10-POS., 2.54mm PITCH, W/CPK, BLACK	1 PC
1	USB 2.0 CABLE, 28 AWG x 1P + 24 AWG x 2C + AEB. UL 2725, BEIGE	A/R
ITEM	DESCRIPTION	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

MCGPVKX21-04B052428R1BG-F8N

SERIES

203mm
FEMALE TO FEMALE
BEIGE
ROUND CABLE
24 /28 AWG
04 TO 10 WAY

DESCRIPTION: USB 2.0 CABLE ASSEMBLY

煜倫股份有限公司

www.morethanall.com