



NOTES

- 1. FREQ. RANGE : DC~4GHz
- 2. IMPEDANCE : 50Ω NOMINAL
- 3. VSWR : 1.15:1 MAX
- 4. CABLE: RG178U
- 5. ATTACHMENT : DIRECT SOLDER

NO	PART NAME	SPECIFICATION	QTY	REMARKS
1	BODY	B60u(C1730 B), TOP PLATING	1	
2	PIN	B60u(C1730 B), Ag PLATING	1	
3	INSULATOR	TEFLON(PTFE)	1	
4	SOLDER BODY	Bs(C3604 BD), TOP PLATING	1	
5	CAP	Bs(C3604 BD), TOP PLATING	1	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1:1
DATE
SIZE A4 PROJECTION

0.5-5 =±0.2
5-30 =±0.4
30-120 =±0.6
120-315 =±1
315-1000 =±1.6
1000-2000 =±2.4

照片框

ORDER INFORMATION

MCX-PCRPE1-178-LF
SERIES | | | LEADFREE
| | | RG178
| | | PANEL EAR
| | | 90°
| | | CRIMP
| | | PLUG

DESCRIPTION: MCX plug R/A dip 90 for RG178U