



5	STRAIN RELIEF	1	PVC		UL94V-0
4	CARRIER ENCLOSURE	1	ABS [777D]		UL94HB
3	DISTANCE SLEEVE	1	BSR-H (0.4t) [C2680R]	NICKEL	30-50u"
2	CONTACT TERMINAL	4	BSR-H (0.2t) [C1519R-H]	TIN PLATED	30-50u"
1	FEMALE INSERT	1	NYLON [101]		UL94V-2
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

SPECIFICATIONS	
Contact resistance	30mΩ Max.
Dielectric strength	500V AC RMS for 1 Minute
Insulation resistance	50MΩ Min. at 250V DC
Rating	7.5A MAX. @ 48V DC
Insertion Force	5.0kg MAX.
Extraction Force	0.1kg~5kg

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

MDA-SA-04-LF
SERIES | LEADFREE
04 WAY
ASSEMBLY
FEMALE

DESCRIPTION: