



对插口位置

Recommended P.C.B Layout (Component Side)

MATERIAL:

INSULATOR: PBT, UL 94V-0, BLACK
 SHELL: ALLOY COPPER, OVER Ni 15 μ Min
 CONTACT: ALLOY COPPER, Au g/f PLATING ON CONTACT AREA.
 30 μ MIN. Sn PLATING ON SOLDER TAIL AREA.
 15 μ MIN. NICKEL UNDERPLATING OVERALL.

ENVIRONMENTAL:

OPERATING TEMPERATURE: -25°C~+85°C

ELECTRICAL:

CONTACT CURRENT RATING: 1.5 Amp
 DIELECTRIC WITHSTANDING : AC 500V/min.
 INSULATION RESISTANCE: 500M Ω min.
 CONTACT RESISTANCE: 30m Ω Max

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
 .X \pm 0.38
 .XX \pm 0.25
 .XXX \pm 0.15
 ANG \pm 2°

P PROJECTION



ORDER INFORMATION

MDJ-F-06-LF
 SERIES | LEADFREE
 06 WAY
 FULL METAL

DESCRIPTION: 迷你單層6P母半金黑色 銅殼鍍無嘜 不加彈 PBT RoHS