



Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 100M Ohm Min. AT 500V DC
 Rated Voltage And Current: DC12V.2A Max;AC 100V.1A Max
 Dielectric Withstanding Voltage:250V AC For 1 Minute
 Durability (Life Test): 100 Cycles
 Insertion Force:4.0KG Maximum.
 Extraction Force:0.9KG Minimum.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	PBT G.F.	BLACK	1
2	CONTACT	PHOS. BRONZE T:0.2	Gold:1~3u", NI:40~60u", TIN:120u" (100% pure Tin of lead free plating)	9
3	SHIELD \	BRASS T:0.3	TIN PLATED Sn:120~200u"	1
4	BOTTOM COVEP	PBT G.F.	BLACK	1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.38

.X ± 0.25

.XX ± 0.13

.XXX ± 0.05

ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MDJ-F-09-LF
 SERIES | T LEADFREE
 09 WAY
 FULL METAL

DESCRIPTION: MINI DIN JACK FLAT 9 PIN DIP