



MATERIALS:

- 1.INSULATOR: LCP UL94V-0,BLACK.
- 2.CONTACT: Brass, Gold/Tin plated or Tin plated
- 3.SHELL: Brass, Tin/nicket plate
- 4.SPRING GROUND: SUS304

ELECTRICAL

- 1.CONTACT CURRENT RATING: 1 Amp.MAX.
- 2.DIELECTRIC WITHSTANDING: AC 1000V MIN. Per minute.
- 3.INSULATION RESISTANCE: 500MΩ MIN. at 500V DC
- 4.CONTACT RESISTANCE: 30mΩ Max.

* Max Processing Temp: (260° for 7 seconds)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MDJ-F-10A-LF
SERIES | LEADFREE
10 WAY A TYPE
FULL METAL

DESCRIPTION: 迷你單層10P母特殊型半金黑鐵殼鍍半鎳錫無嗒不加彈(LCP)