



P.C.B. LAYOUT
BOTTOM VIEW

MATERIAL
 INSULATOR: PBT UL 94V-0 Or LCP
 SHELL: Brass OR Spcc, Tin Plated
 CONTACT: Brass, Gold/Tin plated
 ENVIRONMENTAL
 OPERATING TEMPERATURE: -55°C~+105°C
 ELECTRICAL
 CONTACT CURRENT RATING: 1 Amp
 DIELECTRIC WITHSTANDING : AC 500V/min.
 INSULATION RESISTANCE: 500MΩmin.
 CONTACT RESISTANCE: 30mΩ Max

備注:重點尺寸標示區

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±
 .X±
 .XX±
 .XXX±
 ANG±

PPOJECTION

照片框

ORDER INFORMATION

MDJ-FGR-06-LF
 SERIES | LEADFREE
 | 06 WAY
 | GREEN
 | FULL METAL

DESCRIPTION: 銅殼鍍錫無磷 不加彈 PBT RoHS 迷你單層6P母半金綠(3405U)