

**Specification:**

**Contact Resistance: 30m Ohm Max.**

**Insulation Resistance: 100M Ohm Min.AT 500V DC**


**Rated Voltage And Current: DC12V.2A Max;AC 100V.1A Max**

**Dielectric Withstanding Voltage: 250V AC For 1 Minute**

**Durability (Life Test): 100 Cycles**

**Insertion Force: 4.0KG Maximum.**

**Extraction Force: 0.9KG Minimum.**



NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	PBT G.F.	BLACK	1
2	CONTACT	PHOS. BRONZE T:0.2	Gold:1~3u"; NI:40~60u"; TIN:120u" (100% pure Tin of lead free plating)	6
3	SHIELD	BRASS T:0.3	TIN PLATED Sn:120~200u"	1
4	BOTTOM COVER	PBT G.F.	BLACK	1

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30

.X ± 0.38

.XX ± 0.25

.XXX ± 0.13

ANG ±

P PROJECTION

照片框

**ORDER INFORMATION**

MDJ-FK-06-LF  
SERIES | LEADFREE  
| 06 WAY  
| KINK  
| FULL METAL

DESCRIPTION: MINI DIN JACK FLAT 6 PIN DIP