



Specification:

Contact Resistance: 30m Ohm Max.

Insulation Resistance: 100M Ohm Min. AT 500V DC

Rated Voltage And Current: DC12V.2A Max; AC 100V.1A Max

Dielectric Withstanding Voltage: 250V AC For 1 Minute

Durability (Life Test): 100 Cycles

Insertion Force: 4.0KG Maximum.

Extraction Force: 0.9KG Minimum.

NO.	NAME	MATERIAL	FINISH	Q'TY
1	HOUSING	NYLON 9A9T G.F.	BLACK	1
2	CONTACT	PHOS. BRONZE T:0.2	Gold:1~3u"; Ni:40~60u"; IN:120u" (100% pure Tin of lead free plating)	8
3	SHIELD	BRASS T:0.3	TIN PLATED Sn:120~200u"	1
4	BOTTOM COVER	NYLON 9A9T G.F.	BLACK	1
5	ODD/DIDAL PARTICLE	P.E.	WHITE	1
6	CONTACT	PHOS. BRONZE T:0.4	Gold:1~3u"; Ni:40~60u"; IN:120u" (100% pure Tin of lead free plating)	1
7	SPRING SHIELD	STAINLESS T:0.15		1

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MDJ-FS4NL-09-LF
SERIES | LEADFREE
| 09 WAY
| NYLON
| SPRING
| FULL METAL

DESCRIPTION: MINI DIN JACK FLAT 9 PIN DIP

煜倫股份有限公司

www.morethanall.com