



備註 / NOTE:

1. 安規 / SAFETY:

- 1-1. 規格 / RATING: 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗 / INSULATION RESISTANCE: 50MΩ MIN at 250V DC
- 1-3. 絕緣耐壓 / WITHSTANDING: 250V AC at 1 MINUTE

2. 材質 / MATERIAL:

- 2-1. 外套 / PLASTIC COVER: ABS
- 2-2. 銅管 / SHELL: 黃銅 / BRASS
- 2-3. 塑鋼單腳 / POM RING: POM
- 2-4. 膠芯 / HOUSING: PBT
- 2-5. 針 / PIN: 黃銅 / BRASS
- 2-6. 彈簧 / SPRING: 鋼 / STEEL
- 2-7. 後套 / METAL CAP: 黃銅 / BRASS

3. 電鍍 / PLATING:

- 3-1. 銅管 / SHELL: 鍍 / NICKEL
- 3-2. 針 / PIN: 表金 / Gold Flash
- 3-3. 彈簧 / SPRING: 鍍 / NICKEL
- 3-4. 後套 / METAL CAP: 錫 / TIN

4. 拉拔力 / STRENGTH:

- 4-1. 退針拉力 / STRENGTH of UNLOAD PIN: 2.5kgf MIN
- 5. 不可有射出縮水或缺料現象
- 6. 不可變形
- 7. 不可缺針

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

DRAWING BY CY		X.±
CHECKED BY GENIUS		.X±
UNIT / mm	SCALE 1:1	.XXX±
DATE		ANG±

X.±
.X±
.XXX±
ANG±

照片框

ORDER INFORMATION

MDL-P-07-LF
SERIES | LEADFREE
07 WAY
MALE

www.morethanall.com

SIZE A4

PJECTION

DESCRIPTION: LOCK 7P 無字成品系列