



ELECTRICAL CHARACTERISTICS:
 RATING: 100V AC 1A MAX OR
 12V DC 2A MAX
 INSULATION RESISTANCE:
 50Mohm MIN AT 250V DC
 DIELECTRIC STRENGTH:
 250V AC/1 minute

| | | | |
|----|-------------------|----|---------------------------------------|
| 3 | SHELL | 1 | BRASS, THK=0.4MM NICKEL PLATED |
| 2 | INSULATOR | 1 | PBT, UL 94 V-0 |
| 1 | SOCKET CONTACT | 10 | PHOSPHOR BRONZE PLATING: SEE TABLE |
| 項次 | 名稱 | 數量 | 規格 |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

P PROJECTION

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

照片框

ORDER INFORMATION

MDM-S-10-LF
 SERIES | T LEADFREE
 10 WAY
 FEMALE

DESCRIPTION: