



9	PLASTIC TRAIL	1	PVC		
8	SPRING	1	SWP-B (0.6D)	STAIN	
7	LATTER BODY	1	ABS [ 777D ]		94HB
6	MAIN BODY	1	ABS [ 777D ]		94HB
5	SIDE COVER	1	BSR-H (0.4t) [ C2680R ]	NICKEL	
4	MAIN COVER	1	BSR-H (0.4t) [ C2680R ]	NICKEL	
3	SLIDE RING	1	TEPCON [ M90 ]		
2	CONTACT TERMINAL	4	BSR-H (1.5D) [ R-35 ]	SILVER PLATED	
1	PLASTIC CORE	1	NYLON [ 101 ]		UL94V-2
P/N	PART NAME	Q'TY	MATERIAL	PLATING	REMARKS

#### SPECIFICATIONS

Rating:	20V DC 7.5A Max.
Insulation resistance	DC 250V 50M $\Omega$ Min.
Voltage Withstanding	AC 250V 1 Minute
Insertion force	5Kg Max.
Withdrawal force	1 ~ 5Kg
Endurance insertion extraction	5,000 cycles

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION

照片框

ORDER INFORMATION

MDP-PA2-04-LF  
SERIES | LEADFREE  
| 04WAY  
ASSEMBLY  
MALE

DESCRIPTION: