



備註 / NOTE:

1. 安規 / SAFETY:

- 1-1. 規格 / RATING: 100V AC MAX or 12V DC 2A MAX
- 1-2. 絕緣阻抗 / INSULATION RESISTANCE: 50MΩ MIN at 250V DC
- 1-3. 絕緣耐壓 / WITHSTANDING: 250V AC at 1 MINUTE

2. 材質 / MATERIAL:

- 2-1. 膠芯 / HOUSING: PBT (黑色 / BLACK)
- 2-2. 針 / PIN: 黃銅 / BRASS
- 2-3. 銅管 / COVER: 黃銅 / BRASS
- 2-4. 彈片 / SPRING: 磷銅 / PHOSPHOR BRONZE

3. 電鍍 / PLATING:

- 3-1. 針 / PIN: SEE TABLE A
- 3-2. 銅管 / SHELL: 鍍 / NICKEL
- 3-3. 彈片 / SPRING: 銀 / SILVER

4. 拉拔力 / STRENGTH:

- 4-1. 總合拉拔力 / PULL STRENGTH: 與公座拉拔力五次之後拉力為 1.0kgf~4.0kgf MIN

5. 外觀 / SURFACE:

- 5-1. 針 / PIN:
 - 5-1-1. 不可缺針
 - 5-1-2. 不可壓傷變形
 - 5-1-3. 不可刮傷露銅
- 5-2. 膠芯 / HOUSING:
 - 5-2-1. 不可有射出缺料或縮水現象
 - 5-2-2. 內孔不可阻塞
- 5-3. 銅管 / SHELL:
 - 5-3-1. 刮痕不可過於明顯
 - 5-3-2. 不可有電鍍花紋
 - 5-3-3. 不可刮傷露銅
 - 5-3-4. 鍍層電鍍層部份不可脫落
- 5-4. 彈片 / SPRING:
 - 5-4-1. 不可彎曲變形

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1:1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MDS-S-09-LF
SERIES | T LEADFREE
| 09 WAY
SOCKET

DESCRIPTION: