



NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL/CSA 2651#28 灰 排線	1pcs	
		26P PH:1.0		
2	DIP:	26P(兩件式)BLACK PH:2.0	1pcs	
3	IDC:	26P 有凸點 有SR (兩件式) BLACK PH:2.0	2pcs	
4				

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MF2MIPX3-2626-A22C5-LF

SERIES

LEADFREE

225mm  
FEMALE TO MALE  
26 TO 26 WAY

DESCRIPTION: CABLE ASS"Y