



### PIN DEFINITION

| CN1 | CN2 |
|-----|-----|
| 1   | 1   |
| 2   | 2   |
| 3   | 3   |
| 4   | 4   |
| 5   | 5   |
| .   | .   |
| .   | .   |
| .   | .   |
| 37  | 37  |
| 38  | 38  |
| 39  | 39  |
| 40  | 40  |

MF2X2-4040-F6N-LF  
LEADFREE

RoHS Compliant

| NO | DESCRIPTION  | COLOR | Q'TY | UNIT |
|----|--|-------|------|------|
| 3  | IDC 40PIN MIDDLE COVER (PH1.0) "ROHS"                            | BLACK | 2    | PCS  |
| 2  | IDC 40PIN CONNECTOR PH2.0MM WITH NOSE G/F "ROHS"                 | BLACK | 2    | PCS  |
| 1  | FLAT CABLE 40PIN UL2651 28AWG PH1.0mm WITH RED LINE KT/HF "ROHS" | GREY  | 153  | MM   |



PART NO. MF2X2-4040-F6N

DWG NO. MF2X2-4040-F6N

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2  
.XX ±  
.XXX ±  
AWG

DESCRIPTION:

2.0 IDC 40P/40P W/O SR L:6"

AREA

REVISIONS

HK

DATE

煜倫股份有限公司