


WIRING TABLE

FROM P1	TO P2	WIRE COLOR
1	8	RED
2	7	ORANGE
3	6	BLACK
4	5	WHITE
5	-	-
6	-	-
7	3	BLUE
8	-	-
9	1	GREEN
10	16	RED
11	15	RED
12	14	RED
13	13	RED
14	12	BLACK
15	11	BLACK
16	10	BLACK
17	9	BLACK
18	-	-

DETAIL "B"
FOR ALL WIRES



	DESCRIPTION	BATM P.No	QTY
1	CON.2X9 MINI-FIT FEMALE 0.165" FOR PANEL	PN000480	1
2	CON.2X8 MINI-FIT FEMALE 0.165"	PN000475	1
3	SOCKET TER FOR MINI FIT, FOR WIRES 18-24AWG	PN000461	28
4	RED WIRE 22 AWG UL1007 300V	WR0000017	L=5x120±5mm
5	BLACK WIRE 22 AWG UL1007 300V	WR0000002	L=5x120±5mm
6	ORANGE WIRE 22 AWG UL1007 300V	WR0000001	L=120±5mm
7	BLUE WIRE 22 AWG UL1007 300V	WR0000005	L=120±5mm
8	WHITE WIRE 22 AWG UL1007 300V	WR0000018	L=120±5mm
9	GREEN WIRE 22 AWG UL1007 300V	WR0000019	L=120±5mm
10	Tie Wrap 10cm	XW0000008	2

RoHS compliant component
The use of non-ROHS components or materials during the production process is forbidden

NOTE:
1. CUT AND STRIP ALL WIRES AS SHOWN IN DETAIL "A" ABOVE.

MFMFB-B8B922-F12C-LF
LEADFREE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MFMFB-B8B922-F12C

DWG NO. MFMFB-B8B922-F12C

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE

.X ± 0.2
.XX ±
.XXX ±
AWG


DESCRIPTION:

焯倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE