



NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	COAXI CABLE:	Tinned copper wire braided Silver JACFET: BLACK OD:Ø1.13	1pcs	
2	CONN:	RPSMA 母頭公PIN G/F	1pcs	
3	CONN:	20278-111R-13 G/F	1pcs	
4	H.S TUBE:	3.5Ø*15mm F32 黑	1pcs	
5				
6				
7				
8				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

MHFRPSMA-1R1S113-E9C5-LF

SERIES

LEADFREE

95mm

MALE TO FEMALE

1.13mm DIA CABLE

RT/ST

DESCRIPTION: CABLE ASS"Y