



NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	COAXI CABLE:	Tinned copper wire braided Silver	1pcs	
		JACFET: BLACK OD:Ø1.13		
2	CONN:	SMA 母頭 G/F	1pcs	
3	CONN:	20278-111R-13 G/F	1pcs	
4	H. S TUBE:	3.5Ø*15mm F32 黑	1pcs	
5				
6				
7				
8				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

MHFSMA-1R1S113-E9C5-LF

SERIES

LEADFREE

95mm

MALE TO FEMALE

1.13mm DIA CABLE

RA/ST

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS"Y