

MHFX1-1R1X113-M5C3-LF
LEADFREE

RoHS Compliant

General requirement:

- 1>Solder meeting SGS Europe Directive criteria
- 2>Frequency rating pass IEEE802.11 3Ghz rating
- 3>Insertion Lost<0.8db [sampling test]
- 4>each cable shall pass 100% continuity and Open/short test
- 5>Solder dip on both shield sleeve and the center conductor wire tinned
- 6>Plating on connector shell : Silver
- 7>Plating on contact : gold

ITEM	QYT	DESCRIPTION	MATERIALS	REMARK
2	1	CONNECTOR	I-PEX MALE R/A	EQUIVALENT
1	1	WIRE	COAXIAL 1.13 ϕ BLACK(I-PEX)	EQUIVALENT



PART NO. MHFX1-1R1X113-M5C3

DWG NO. MHFX1-1R1X113-M5C3

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X \pm 0.2
.XX \pm
.XXX \pm
AWG

DESCRIP TION: RF CABLE I-PEX 1.13 TO TIN L:53mm

AREA

REVISIONS

HK

DATE

焜倫股份有限公司