



NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

| NO. | ITEM.        | DESCRIPTION                       | Q'TY | UL/CSA No. |
|-----|--------------|-----------------------------------|------|------------|
| 1   | COAXI CABLE: | Tinned copper wire braided Silver | 1pcs |            |
|     |              | JACFET: BLACK OD:Ø1.13            |      |            |
| 2   | CONN:        | 20278-111R-13 G/F                 | 1pcs |            |
| 3   |              |                                   |      |            |
| 4   |              |                                   |      |            |
| 5   |              |                                   |      |            |
| 6   |              |                                   |      |            |
| 7   |              |                                   |      |            |
| 8   |              |                                   |      |            |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION



ORDER INFORMATION

MHFX1-1R1X113-M6N-LF

SERIES

R/A

LEADFREE

152.4mm

MALE

1.13mm

DESCRIPTION: CABLE ASS"Y