



General requirement:

- 1>Solder meeting SGS Europe Directive criteria
- 2>Frequency rating pass IEEE802.11 3Ghz rating
- 3>Insertion Lost<0.8db [sampling test]
- 4>each cable shall pass 100% continuity and Open/short test
- 5>Solder dip on both shield sleeve and the center conductor wire tinned
- 6>Plating on connector shell : Silver
- 7>Plating on contact : gold

2	1	CONNECTOR	I-PEX	EQUIVALENT
1	1	WIRE	COAXIAL 1.32 ϕ BLACK(HITACHI)	EQUIVALENT
ITEM	QYT	DESCRIPTION	MATERIALS	REMARK

MORETHANALL
CONNECTORS
ASSEMBLIES

焯倫股份有限公司

PART NO. MHFX1-1R1X132-M10C3		CHECKED BY CY	TOLERANCES ARE .X \pm 0.2 .XX \pm .XXX \pm AWG
DWG NO. MHFX1-1R1X132-M10C3			
FILE NO.		DRAWING BY	PROJECTION
UNIT / mm	SCALE 1:1		

DESCRIP TION:	I-PEX + COAXIAL 1.32 ϕ + 脫鍍 L:103mm			
AREA	REVISIONS	HK	DATE	