



- FEATURES:**
- . 2-15 Circuits
  - . PBT UL 94V-0

- SPECIFICATIONS:**
- . Current rating: 2A AC, DC
  - . Voltage rating: 500V AC, Maximum
  - . Temperature range: -40°C ~ +105°C
  - . Contact resistance: Initial Value/10m ohm max.  
After environmental testing/20m ohm max.
  - . Insulation resistance: 1000 M ohm min
  - . Withstand Voltage: 1500V AC/minute

CKT	A	B	C
2	2	5.1	6
3	4	7.1	8
4	6	9.1	10
5	8	11.1	12
6	10	13.1	14
7	12	15.1	16
8	14	17.1	18
9	16	19.1	20
10	18	21.1	22
11	20	23.1	24
12	22	25.1	26
13	24	27.1	28
14	26	29.1	30
15	28	31.1	32

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±

PJECTION

照片框

**ORDER INFORMATION**

MI-R-xx-LF  
SERIES | LEADFREE  
02-15 WAY  
DIP 90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: