


WIRE DIAGRAM



ELECTRONIC TEST:

1. 100% TEST, (Open, Short, Miss Wire).
2. Conduct Resistance: 5 Ω/ max.
3. Insulation Resistance: 10M Ω /min.
4. Hi-Pot: 300v /10ms.

5	MICRO HDMI D COVER TRANSPARENT	2	PCS
4	BLACK PVC 45P.		g
3	MICRO USB:5P GOLD 1U" CONNECTOR, NICKEL PLATED SHELL, PLASTLC:BLACK.		g
2	MICRO HDMI M 19P SOLDER TYPE BLACK INSULATION SHELL GOLD FLACH, PIN 1U" COLD PLATED	1	SET
1	CABLE: 28**4C OD3.0MM BLACK L=1000MM.	L	PCS
ITEM	STANDARD SPECIFICATION		Q' TY UNIT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

MIBMIH-5B1928-M1M-LF

SERIES

LEADFREE
1000mm
MALE TO MALE
28 AWG
5 PIN B TYPE TO 19 WAY

DESCRIPTION: MICRO HDMI D TO MICRO USB5P/M CABLE BLACK L=1000MM.