

SEC A-A

USB3.0 BF	MCBM	COLOR
1	1	RED
2	2	WHITE
3	3	GREEN
4	5	BLACK
5	6	YELLOW
6	7	BLUE
7	8	DRAIN
8	9	ORANGE
9	10	PURPLE
SHELL	SHELL	BRAID

ELECTRICAL PROPERTIES:

- 100% OPEN SHORT MIS-WIRE TEST
- Contact Resistance:10ohm
- Insulation Resistance:5Mega ohm
- Hipot test:300V/10ms

QTY	UNIT	DESCRIPTION
1	pcs	4 USB3.0 MICRO B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F
1	pcs	3 55P PVC MOLD BLUE IN COLOR
2	pcs	2 USB3.0 B TYPE FEMALE SHELL PLATED:NICKEL CONTACT:G/F
1	pcs	1 UL20276 (1P*28#+D+AL+Mya1r)*2C+1P*28#+2C*28#+AL+B DD:5.5±0.15mm BLUE IN COLOR

MIBUB-10B9B-E50C-LF
LEADFREE

RoHS Compliant

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MIBUB-10B9B-E50C

DWG NO. MIBUB-10B9B-E50C

CHECKED BY CY

TOLERANCES ARE

FILE NO.

DRAWING BY

.X ± 0.2
.XX ±
.XXX ±
AWG


DESCRIPTION:

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE