



ELECTRONIC TEST:  
 1.OPEN/SHORT/INTERMITTE:100%.  
 2.INSULATION RESISTANCE:10MΩ  
 3.CONTACT RESISTANCE:3Ω  
 4.HI-POT:250V DTAGE.

Pin Assignment		
USB AM	SIGNAL NAME	MICRO USB AB F
1	VBUS	1
2	D-	2
3	D+	3
	ID	4
4	GND	5
SHELL	SHIELD	SHELL

4	USB A TYPE MALE SHELL PLATED NICKEL CONTACT:G/F	PCS	1
3	INTERNAL WIRES: UL1007 30AWG	PCS	5
2	PVC MOLDED COLOR: BLACK		
1	MICRO USB-AB TYPE FEMALE GRAY PASTERN CONTACT PLATED: GOLD FLASH	PCS	1
NO.	DESCRIPTION	UNIT	QT'Y

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES  
 煜倫股份有限公司  
 www.morethanall.com

RoHS Compliant

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1:1  
 DATE  
 SIZE A4 PPROJECTION

TOLERANCES ARE

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

照片框

ORDER INFORMATION

MIBUB-AM-5AB4A-LF  
 SERIES MOLDING FEMALE TO MALE  
 LEADFREE  
 5AB TO 4A

DESCRIPTION: