




Features:

- 2 ~ 12 circuits available
- Material: LCP
- Tin-plated brass pin

Specification:

- Current rating: 5A AC, DC
- Voltage rating: 250V AC, DC
- Contact resistance: 10mΩ Max.
- Dielectric withstanding voltage: 1500V AC/minute
- Ambient temperature range: -25°C ~ 85°C



PCB Layout: Component side

&& xx = 02 ~ 12

Dimensional Information

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2	3.0	9.65	4	9.0	15.65	6	15.0	21.65	8	21.0	27.65	10	27.0	33.65	12	33.0	39.65
3	6.0	12.65	5	12.0	18.65	7	18.0	24.65	9	24.0	30.65	11	30.0	36.65			

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X, ±
.X ± 0.25
.XX ± 0.15
.XXX ± 0.05
ANG ±

PPOJECTION

照片框

ORDER INFORMATION


MIF-PWXR-1Xxx-LF

SERIES
MALE
90°SMT
LEADFREE
1X02:02 WAY
1X12:12 WAY
REEL
NON EAR

DESCRIPTION:

SALES LEADS AND PRODUCT REQUEST FORM

SPEC NO: _____



NOTE:

- 1.10 Sprocket hole pitch cumulative tolerance ± 0.2 m/m.
- 2. Carrier camber is within 1mm in 250mm
- 3. Material: Black Conductive polystyrene Alloy.
- 4. A_o and B_o measured on a plane 0.3mm above the bottom of the pocket.
- 5. K_o measured from a plane on the inside bottom of the pocket to the top surface of the carrier.
- 6. Pocket position relative to sprocket hole measured as true position of pocket, not pocket hole.

RATIO 1:1

ITEM	SPEC
W	32 $+0.30$ -0.30
Ao	10.3 $+0.10$ -0.10
Bo	16 $+0.10$ -0.10
Ko	9.5 $+0.10$ -0.10
P	16.0 $+0.10$ -0.10
F	14.2 $+0.10$ -0.10
E	1.75 $+0.10$ -0.10
D	1.50 $+0.10$ -0.00
D1	1.50 $+0.25$ -0.00
Po	4.00 $+0.10$ -0.10
P2	2.00 $+0.10$ -0.10
t	0.40 $+0.05$ -0.05

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, $\pm$
X, $\pm$
.XX $\pm$
.XXX $\pm$
ANG $\pm$

照片框

ORDER INFORMATION

MIF-PWXR-1Xxx-LF

SERIES

MALE

90°SMT

REEL

NON EAR

LEADFREE

1X02:02 WAY

1X12:12 WAY

DESCRIPTION: