

P1
MIC-8P ϕ 16mm FEMALE

P3

P2
MX3.0-2*4PH

MIF2XLR-0808-F40C-LF
LEADFREE

WIRING DIAGRAM

	P1	P2	P3
RED	1	1	RED
BLUE	2	3	BLUE
GREEN	3	5	GREEN
YELLOW	4	7	YELLOW
WHITE	5	4	WHITE
BLACK	6	6	BLACK
BROWN	7	2	BROWN
PURPLE	8	8	PURPLE
D			D

RoHS Compliant

NO.	PART NO.	Q'TY	UNITS	DESCRIPTION
6	TERMINAL	1	PCS	RED 5.5mm RING LUG
5	TERMINAL	8	PCS	MX3.0-TP-FEMALE
4	HOUSING	1	PCS	MX3.0-2*4PH-MALE
3	TUBE	8	PCS	SHRINK TUBE ϕ 2.5*10mm #BK
2	CONNECTOR	1	PCS	MIC 8P JACK ϕ 16mm
1	CABLE	480	mm	UL2464 24AWG 8C+AE OD:6.0mm #BLACK

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MIF2XLR-0808-F40C

DWG NO. MIF2XLR-0808-F40C

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X \pm 0.2
.XX \pm
.XXX \pm
AWG

DESCRIPTION: MIC 8P /2*4PH/0.7M

AREA

REVISIONS

HK

DATE

煜倫股份有限公司