



#### NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

#### ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

| A     | COLOR | B  |
|-------|-------|----|
| 1     | BLACK | 1  |
| 2     | WHITE | 2  |
| 3     | RED   | 3  |
| 4     | GREEN | 4  |
| SHELL | BRAID | NC |

| NO. | ITEM.        | DESCRIPTION                                     | Q'TY |
|-----|--------------|-------------------------------------------------|------|
| 1   | WIRE:        | UL2725 #28*1PR(WHITE, GREEN)+#24*2C(RED, BLACK) | 1PCS |
|     |              | +AEB JACKET:BLACK USB2.0 OD:4.5                 |      |
| 2   | CONN:        | USB A TYPE MALE 4P WHITE 30U"                   | 1PCS |
| 3   | MOLDED:      | PVC 45P BLACK Module Number:GH-491              | 8.5G |
| 4   | HOUSING:     | MIF-SH-2X02                                     | 1PCS |
| 5   | TERMINAL:    | MIF-FT-26                                       | 4PCS |
| 6   | SHRINK TUBE: | 5Ø*20mm BLACK F32                               | 1PCS |

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

#### ORDER INFORMATION

MIFUB-B024A2428R1-A60C-LF

SERIES

LEADFREE

600mm

FEMALE TO MALE

ROUND CABLE

24,28 AWG

04 TO 4 PIN A TYPE

DESCRIPTION: CABLE ASS'Y