

Specifications:
 Current Rating:1.0A AC/DC
 Voltage Rating:30V AC/DC
 Contact Resistance:20m ohm. Max.
 Insulation Resistance:1000M ohm. Min.
 Withstanding Voltage:500V AC For One Minute
 Operating Temperature Range:-40°C ~ +105°C
 Material and Finish
 Insulator:High Temp. Plastic (UL94V-0)
 Contact:Copper Alloy
 Finish:Tin Plated

Circuits	Dimension		Circuits	Dimension	
	A	B		A	B
4	8.45	2.54	16	23.69	17.78
6	10.99	5.08	18	26.23	20.32
8	13.53	7.62	20	28.77	22.86
10	16.07	10.16	22	31.31	25.40
12	18.61	12.70	24	33.85	27.94
14	21.15	15.24	26	36.39	30.48

MIM-BCR-xx-LF
 LEADFREE

RoHS Compliant

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫股份有限公司

PART NO. MIM-BCR-xx

DWG NO. MIM-BCR-xx

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X±0.2
 .XX±0.1
 .XXX±
 AWG

DESCRIP TION:


2.54mm IDC Connector Male
 On Wire Type

AREA


REVISIONS

HK

DATE





MIM-BCR-xx




Note:


- 1.All dimensions meet EIA-481-3 requirements.
- 2.Material : Black Conductive Polystyrene Alloy 100% recyclable.
- 3.Thickness : 0.40±0.05mm
- 4.Component load per 13" reel :700 pcs.
- 5.CARTON SIZE:350*350*296(MM)



For Reel width (dimension W)16,24mm ,Single row hole



For Reel width (dimension W)32,44,56,72mm ,Double rows hole



Pin No	W	A	PCS/R	R/CTN	Q'TY
04	16	21	700	12	8400
06	24	29	700	9	6300
08	24	29	700	9	6300
10	32	37	700	7	4900
12	32	37	700	7	4900
14	44	49	700	5	3500
16	44	49	700	5	3500
18	44	49	700	5	3500
20	44	49	700	5	3500
22	44	49	700	5	3500
24	56	61	700	4	2800
26	56	61	700	4	2800

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MIM-BCR-xx		CHECKED BY CY	TOLERANCES ARE .X ± 0.2 .XX ± .XXX ± AWG	DESCRIPTION: 2.54mm IDC Connector Male On Wire Type Packing list		
DWG NO. MIM-BCR-xx						
FILE NO.		DRAWING BY	AREA	REVISIONS	HK	DATE
UNIT / mm	SCALE 1:1	PROJECTION				

煜倫股份有限公司