



NOTE:
 1.SAFETY:
 1-1.RATING: 0.5A/250Vac.
 1-2.CONTACT RESISTANCE: 30mOhm MAX.
 1-3.INSULATION RESISTANCE: 100Mohm MIN.
 1-4.DIELECTRIC WITHSTANDING VOLTAGE: 100Vac/1minute.
 1-5.DURABILITY: 10,000cycles.
 2.MATERIAL:
 2-1.PIN:PHOSPHOR BRONZE.
 2-2.HOUSING:NYLON COLOR:TABLE A \triangle \triangle
 2-3.LATCH:STAINESS #304.
 2-4.SHELL:STAINESS #304.. \triangle
 2-5.COVER:NYLON 66 COLOR:BLACK. \triangle
 3.PLATING:
 3-1.PIN:GOLD 15u" MIN ON CONTACT AREA,
 TIN 100u" MIN ON SOLDER TAILS,
 UNDERPLATED NICKEL OVER ALL 60u" MIN.
 3-2.SHELL:NICKEL OVER ALL 60u" MIN.

TABLE A \triangle

MISB-PAxx-5A-LF
 BK:BLACK LEADFREE
 WH:WHITE

RoHS Compliant

MISB-PABK-5A	MICRO USB 5PIN(M) A TYPE	黑色
MISB-PAWH-5A	MICRO USB 5PIN(M) A TYPE	白色
P/N	PLATED	HOUSING

MORETHANALL
 CONNECTORS
 ASSEMBLIES

煜倫股份有限公司

PART NO. MISB-PAxx-5A		CHECKED BY CY		TOLERANCES ARE		DESCRIPTION: MICRO USB 5PIN(M) A TYPE				
DWG NO. MISB-PAxx-5A		DRAWING BY		.X ± 0.2		AREA	REVISIONS	HK	DATE	
FILE NO.		PROJECTION		.XX ±						
UNIT / mm	SCALE 1:1			.XXX ±						
				AWG						