



ITEM 項目	PARTS NAME 件名稱	Q'TY	MATERIAL 材質	FINISH/REMARK 處 /備註
1	HOUSING	1	SYNTHETIC RESIN	(Black)
2	CONTACT	5	COPPER ALLOY	Gold flash selective
3	SHELL	1	STAINLESS	Ni 20u"
4	LATCH	1	STAINLESS	Non-plating
5	BACK COVER	1	SYNTHETIC RESIN	(Black)

- NOTES
- 1.MATERIAL: See drawing
 - 2.ELECTRICAL
 - 2.1.Insulator resistance: 1000M ohms Min. @ 250 VDC
 - 2.2.Withstanding voltage: 100 VAC / minute
 - 2.3.Contact resistance: 50m ohms Max.
 - 3.MECHANICAL
 - 3.1.Mating force: 35N(3.50kgf) Max.
 - 3.2.Unmating force: 8N(0.8kgf) Min.
 - 3.3.Durability: 10000 cycles Min.
 - 3.4.Contact retention force: 4.3N(0.43kgf) Min
 - 4.PACKING: 200pcs/tray (reference)

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.30

.XX ± 0.20

.XXX ±

ANG ± 5°

PPOJECTION

照片框

ORDER INFORMATION

MISB-PM13-5B-LF
SERIES | LEADFREE
5 PIN B TYPE
HIGH 13.9mm
MOLDING
MALE

DESCRIPTION: ASS'Y HOUSING Solder type-5position