



P.C.B LAYOUT MOUNTING PATTERN

NOTES:

MATERIAL:

1.1 HOUSING: LCP UL94V-0,Black

1.2 CONTACT: BRASS

1.3 SHELL: BRASS

Finish:

2.1 Contact: Plated Gold in Mating Area ;

Gold Plated on Solder Balls

Nickel under plated overall

3.SPECIFICATION:

3.1 CURRENT RATING: 1.0 A MAX

3.2 DIELECTRIC WITHSTANDING VOLTAGE:

100 V(ac) FOR 1min

3.3 CONTACT RESISTANCE: 50 mΩ MAX.

3.4 INSULATION RESISTANCE: 100 MΩ MIN.

3.5 TOTAL MATING FORCE: 3.57 KgF MAX.

3.6 TOTAL UNMATING FORCE: 1.0 KgF MIN.

3.7 LIFE: 5,000 CYCLES

3.8 TEMPERATURE RANGE: -30°C ~ +80°C

RoHS Compliant

TOLERANCES ARE

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

Up to 5 ±0.2  
Above 5 ~ 15 ±0.3  
Above 15 ~ 30 ±0.4  
Above 30 ~ 50 ±0.5  
Angle ±0.3°

照片框

ORDER INFORMATION

MISB-SWFXME5664P40-5B-LF

SERIES

FEMALE

NON FLANGE

LEADFREE

5 PIN B TYPE

POST 4.0mm

90°SMT

METAL FOOT 5.67mm+EAR 6.40mm

MORETHANALL  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MICRO USB B TYPE 前插5.67 後貼有柱 平口