


MICRO SIM CARD

■ CIRCUIT TRACE KEEP OUT AREA
 ■ SMT SOLDER AREA

THERE SHOULD NOT BE ANY CIRCUITRIES IN THE LAYOUT SPACE OF THE PRODUCTS.

RECOMMENDED PCB LAYOUT
 GENERAL TOLERANCE ±0.05



MATERIALS

HOUSING: HI-TEMP PLASTIC (UL 94V-0)
 SHELL: STAINLESS, NICKEL PLATING
 Au PLATED ON SOLDER TAIL
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA, TIN PLATED ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 100m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 250V
 OPERATION TEMPERATURE: -40°C~+85°C

SIM pin	Assignment
PIN#	Name
C1	VCC
C2	RST
C3	CLK
C5	GND
C6	VPP
C7	I/O

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.25
 .XXX ± 0.15
 ANG ± 2°

PJECTION

照片框

ORDER INFORMATION

MISCP-W15E13A-06-LF

SERIES | LEADFREE
 06 WAY
 SWITCH CLOSED
 1.35mm HIGH
 EAR WIDTH 15.58mm
 90° SMT

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com