



MATERIAL: Specification

Insulator: High Temperature Thermoplastic,
 UL 94V-0.
 Contact: Copper Alloy
 SHELL: SUS

PLATING:

Contact: Plated 50u" Ni Overall Contact Au 1U,
 pad Au
 Shell: Plated 50u" Ni Overall, pad 1u

Electrical:

Current Rating : 0.5Amps.max
 Voltage Rating : 5V AC/DC
 Ambient Temperature Range : -40°C~+85°C
 Storage Temperature Range : -40°C~+85°C
 Ambient Humidity Range : 95% R.H. Max.
 Contact Resistance: 100mΩ max.
 Insulation Resistance: 1000MΩ min./500VDC
 IR Reflow Temperature: 260°C
 Mating Cycles: 3000Min Insertions

RoHS Compliant

TOLERANCES ARE

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ±

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

照片框

ORDER INFORMATION

MISCP-W15E14A-06-LF

SERIES | LEADFREE
 | 06 WAY
 | SWITCH CLOSED
 | 1.42mm HIGH
 | EAR WIDTH 15.10mm
 90°SMT

DESCRIPTION: 1.43H Push Push Micro SIM CARD

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com