



MATERIALS
 HOUSING: LCP (UL 94V-0), BLACK
 SHELL: SUS
 TERMINAL: COPPER ALLOY, GOLD PLATED

SPECIFICATION
 CURRENT RATING: 0.5 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 100m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

MICRO SIM CARD	
Pin No.	NAME
C1	VCC
C2	RST
C3	CLK
C4	RESERVED
C5	GND
C6	VPP
C7	I/O
C8	RESERVED

RoHS Compliant

TOLERANCES ARE

X	± 0.40
.X	± 0.30
.XX	± 0.20
.XXX	± 0.10
ANG	±



ORDER INFORMATION

MISCV-W14EB15X-08-LF
 SERIES | | | | LEADFREE
 | | | | 08 WAY
 | | | | NON POST
 | | | | HIGH 1.5mm
 | | | | DOUBLE EAR
 90°SMT | | | | PAD TO PAD 14.9mm

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DRAWING BY CY		SCALE 1:1
CHECKED BY GENIUS		
UNIT/mm	DATE	
SIZE A4	PJECTION	

DESCRIPTION: MICRO SIM CARD, 8 PIN, PCB MOUNT, SMT, METAL SHIELD, HINGE TYPE, FEMALE