



SCHMATIC

1. Functional spec.	
1.1 Rated Voltage	125/250 VAC ; 5.0 A
1.2 Contact Resistance	≤ 100mΩ (Initial value)
1.3 Operating Force	60 ± 25gf
1.4 Free Position	16.7 ± 0.8 mm
1.5 Operating Position	14.5 ± 0.8 mm
2. Reliable Rating	
2.1 Mechanical Life	1,000,000 CYCLES
2.2 Electrical Life	10,000 CYCLES
2.3 Insulation Resistance	≥ 100MΩ DC 500V (Initial value)
2.4 Withstand Voltage	AC 1,000V 1 minute (Initial value)
2.5 Operating Temper	-25 °C - +85 °C
2.6 Ambient Humidity Used	<70% RH

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

照片框

ORDER INFORMATION

MISW-D87L15J-060-LF

SERIES LEADFREE

60g
J TYPE
LEVEL 15.8mm
CONTACT PITCH 8.8+7.3mm
DIP 180°

DESCRIPTION: MICRO SWITCH