


SCHMATIC DIAGRAM



1. Specifications 技术特性表

RATINGS 额定值	10GPA 125/250VAC μ 40T105 5E4 6A 30VDC
ELECTRONICAL LIFE 电气寿命	10(3)A 125/250VAC μ 40T105 5E4
TEMPERATURE 温度等级	6A 30VDC 40T105 5E4
	10(3)A 250VAC μ 10T105 5E4
INSULATION STRENGTH 绝缘电阻	100M Ω MIN
TEST VOLTAGE 耐电压	AC1000V/2000V
CONTACT RESISTANCE 接触电阻	50m Ω MAX
OPERATING FORCE 动作力	0.45N MAX
RELEASE FORCE 释放力	0.05N MIN
OPERATING POSITION 动作位置	20 \pm 1.2mm
MOVEMENT DIFFERENTIAL 差动行程	1mm MAX

2. Parts List OF TYPE KW3A 零件材质表

No.	Name 名称	Material 材料
1	BUTTON 开关子	Bakelite PF2A5-151(j) 绿色 电木粉
2	LEVER 杠杆	Brass alloy H62, Silver plated 黄铜, 镀银
3	CASE 基座	Plastic PBT(灰色) 工程塑料
4	PLATE MOVING 可动片	Brass alloy H62, Silver plated 黄铜, 镀银
5	TERMINAL 支架	Brass alloy H65, Silver plated 黄铜, 镀银
6	CONTACT 静触点	AgNi10/Cu 银-镍/铜
7	TERMINAL 端子	Brass alloy H65, Silver plated 黄铜, 镀银
8	TERMINAL 端子	Brass alloy H65, Silver plated 黄铜, 镀银
9	CONTACT 动触点	AgNi10/Cu 银-镍/铜
10	SPRING 簧片	Beryllium alloy QBe2 铍青铜
11	MOVING ARMS 动臂	Stainless steel 不锈钢
12	COVER 盖	Plastic PBT(灰色) 工程塑料

3. Safety authentication 安全认证



MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. \pm
.X \pm
.XX \pm
.XXX \pm
ANG \pm

PPOJECTION

照片框

ORDER INFORMATION

MISW-Q4C-075-LF

SERIES LEADFREE

75g

4.7mm TAB x 3pin

DESCRIPTION: MICRO SWITCH